MP65e

BRIGHTNESS
4500 Normal
3800 Eco

RESOLUTION
1024x768 (XGA) True
1280X1024 (SXGA) Compressed

DISPLAY TYPE
0.79” 3-LCD with MLA

CONTRAST RATIO
500:1

LAMP
275w NSH

LAMP LIFE
1500 Lamp Hours (Normal)
2500 Lamp Hours (Eco)

DIAGONAL IMAGE SIZE
40” - 300” Inches

ASPECT RATIO
4:3
16:9 Compatible

Special features of the MP65e include:

Auto Brightness*- Detects ambient light and adjusts brightness, extending lamp life.*

Dust/Smoke Filter - *High-efficiency dust cabinet and air filter perfect for dust-torn environments.*

Quick Start and quick shut down *– Short length when powering the projector on & off.*

Network management *- Manage/ monitor your projector using a wired & wireless (optional) network.*

Auto filter alert - *Projector notifies you when the filers need to be changed.*

OPTIONAL ACCESSORIES:
Optional lenses
RS232 Cable
Universal Ceiling Mount / Ceiling Round Flush Kit
Replacement lamp, Replacement filter

SHIPS WITH:
Remote Control w/ Mouse Pad and Laser Pointer
Two AAA Batteries
User Manual (Quick start Guide & CD-ROM)
Power Cord / Soft carry case
VGA Cable

PROJECTION LENS
Manual Focus/Zoom

ZOOM RATIO
1.2:1 (Standard Lens)

THROW DISTANCE
4’-30’ Feet
1.2-9.1 Meters

THROW RATIO
1.47 ~ 1.78 (Standard)

INPUTS
DVI-I
VGA
Audio Mini Jack x 2
RCA Audio (R/L)
Component
Composite Video
S-Video

OUTPUTS
VGA
Mini jack audio

COMPATIBILITY
VGA, SVGA, XGA, SXGA, MAC

PROJECTOR CONTROLS
Mini Din 8-Pin
RS232 (9-Pin)
USB mouse control
RJ 45

KEYSTONE
+/- 30 Degrees

VIDEO COMPATIBILITY
NTSC, NTSC4.43 , PAL, PAL-M, PAL-N, SECAM, PAL60

EDTV / SDTV / HDTV
480i/p, 525i/p, 576i/p, 625i/p, 720p, 1080i

AUDIO
1 x 8w

DIMENSIONS (WxHxD)
13.1”” x 11.3” x 27.2”
33.3 x 11.3 x 27.2 cm

WEIGHT
16.5 lbs (7.5Kg)

DECIBEL RATING
33 dB Standard
30 dB Eco Mode

WARRANTY
3 year parts & labor/
90 day lamp

FCC CERTIFICATION
Class B

H-SCAN RATE
15—107 kHz

V-SCAN RATE
43—120 kHz

POWER SUPPLY
AC 100~240V, 50/60 Hz

PWR. CONSUMPTION
430w (Typical)

BOXLIGHT CORPORATION

19462 Powder Hill Place, Suite 101
Poulsbo, WA 98370

www.boxlight.com
Direct 800.762.5757
International 360.779.7901
Partners 866.688.3636

© 2007 BOXLIGHT Corporation. All rights reserved. Specifications are subject to change without notice.